

Delivery Program

Product Category:	Accelerometers
Model:	Model MAV52
Order Code(s):	AG928, AG929, AG932

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AG928 + 25,4 mm/s RMS (SA), 50 g, Connector: 3 pin 62GB (AG928), 1/4-28 UNF (17b)	AG928 – SA – 17b	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Sensitivity			25,4 mm/s RMS (SA) (*) 12,7 mm/s RMS; (SB) 50,8 mm/s RMS; (SC) 101,6 mm/s RMS (SD)
Dynamic range			50 g
Electrical termination			Connector: 3 pin 62GB (AG928) Cable: S.S over braided PTFE (AG932) Cable (submersible) (AG929)
Mounting arrangement			17b. 1/4-28 UNF (*) 17c. Quickfit female

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.