

## Delivery Program

<b>Product Category:</b>	Accelerometers
<b>Model:</b>	VM110 & VM120 Vibration Meter Kit
<b>Order Code(s):</b>	AG941, AG942

### USE THE CHART BELOW TO DETERMINE LEAD TIMES<sup>1</sup>

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AG941 Model VM110 vibration meter kit	AG941	<b>Build-to-order, call Honeywell for lead time</b>

	<b>Quick-ship</b> (Ships in 1-5 days)	<b>Fast track manufacture</b> (Ships within 4 weeks)	<b>Build-to-order</b> (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
<b>Acceleration</b>			2G, 20G, 200G
<b>Velocity Range</b>			2in/s, 20 in/s, 200 in/s
<b>Displacement</b>			2 thou, 20 thou, 200 thou
<b>Kit contents</b>			1 ea Vibration mere 1 ea hand held probe 1 ea magnet 1 ea 4 in spike 1 ea carrying case
<b>Accessory</b>			<b>AG902:</b> Model MA11 100 mV/G accelerometer, cable <b>AG901:</b> Model MA11 100 mV/G accelerometer, conn <b>CA42:</b> Coiled cable assembly (2 pin MS to IA110) <b>CA43:</b> Coiled cable assembly (TNC to IA110) <b>2100:</b> Hand held probe <b>CA61:</b> IA110 adapter <b>MM1:</b> Magnet(1/4 in UNF mounting) <b>PS1:</b> Hand held spike (25 mm, ¼ in unF mounting) <b>PS 2:</b> Hand held spike (100 mm, ¼ in unF mounting) <b>PS 3:</b> Hand held spike (150 mm, ¼ in unF mounting) <b>PS 5:</b> Hand held spike (25 mm, ¼ in unF mounting) <b>PS1:</b> Hand held spike (300 mm, ¼ in unF mounting) <b>HE1:</b> Carrying case with foam cut outs

<sup>1</sup> LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

\* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.