

Delivery Program

| | |
|--------------------------|--------------------------|
| Product Category: | Displacement Transducers |
| Model: | DLE, dc-dc |
| Order Code(s): | BY128 |

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

| If you build this: | The order configuration is this: | The delivery class is: |
|--|--|--|
| BY128 $\pm\pm 254$ mm [± 10 in] (HW), Bendix connector on body (TM406), Axial cable exit (TM49), 13/16-32 UNF (TM511), and ± 0.1 % max. linearity (L10) | BY128 – HW – TM406 – TM49 – TM511 – L10 | Build-to-order call Honeywell for lead time |

| | Quick-ship (Ships in 1-5 days) | Fast track manufacture (Ships within 4 weeks) | Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000) |
|-------------------------------------|--|---|---|
| Stroke ranges | | | $\pm 12,7$ mm [± 0.5 in] (HP) $\pm 25,4$ mm [± 1.0 in] (HQ) $\pm 50,8$ mm [± 2.0 in] (HR) $\pm 76,5$ mm [± 3.0 in] (HS) $\pm 101,6$ mm [± 4.0 in] (HT) $\pm 152,4$ mm [± 6.0 in] (HU) $\pm 203,2$ mm [± 8.0 in] (HV) ± 254 mm [± 10 in] (HW) ± 381 mm [± 15 in] (HY) ± 470 mm [± 18.5 in] (HZ) |
| Electrical termination | | | Multiconductor shielded cable (1.83 m [6 ft]) TM405. Axial Bendix connector on body radial (side) TM406. Bendix connector on body |
| Electrical cable orientation | | | TM49. Axial cable exit |
| Mounting threads | | | TM511. 13/16-32 UNF |
| Improved linearity | | | L10. ± 0.1 % max. linearity (less than or equal to ± 101.6 mm [± 4 in]) |

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Fast Track deliveries are 4 to 6 weeks.

Build-to-order deliveries are 8 weeks.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.