

Delivery Program

Product Category:	Displacement Transducers
Model:	M5C, ac-ac
Order Code(s):	AY318

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AY318 $\pm\pm 0,25$ mm [± 0.01 in] (HH), Multiconductor shielded cable, Right angle cable exit (Ra), 3/8-24 UNF threaded sleeve (TM392), ± 0.1 % max. linearity (L10), and 204 °C (TM315)	AY318 – HH – Ra – TM392 – L10 – TM315	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Stroke ranges			$\pm 0,25$ mm [± 0.01 in] (HH) $\pm 0,51$ mm [± 0.02 in] (HI) $\pm 1,02$ mm [± 0.04 in] (HK) $\pm 2,54$ mm [± 0.10 in] (HM) $\pm 5,08$ mm [± 0.20 in] (HN) $\pm 7,62$ mm [± 0.30 in] (HF) $\pm 10,16$ mm [± 0.40 in] (HG) $\pm 12,7$ mm [± 0.50 in] (HP)
Electrical termination			Multiconductor shielded cable (1,83 m [6 ft])
Electrical cable orientation			Ra . Right angle cable exit
Mounting threads			TM392 . 3/8-24 UNF threaded sleeve
Improved linearity			L10 . ± 0.1 % max. linearity (less than or equal to 101,6 mm [± 4.0 in])
Higher temperature			TM315 . 204 °C [400 °F] up to 101,6 mm [± 4.0 in] models

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

Fast Track deliveries are 4 to 6 weeks.

Build-to-order deliveries are 8 weeks.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.