

Delivery Program

Product Category:	Instruments
Model:	GM
Order Code(s):	AE213

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AE213 + GM model, 0.5 to 5 mV/V input range, filter setting (260 Hz) analog output, high low limits (58A) alarm output, peak/hold display options (58C), 110 vac power supply	AE213 – 58A – 58C	Quick ship, ships in 1 to 5 days
AE213 + GM model, 5 to 50 mV/V input range (52C), optional filter (58T), peak and hold alarm output (58C), track/hold display options (58D), 220 vac power supply (60A), rack mount (51A)	AE213 – 52C - 58T - 58C - 58D - 60A - 51A	Fast-track manufacture, ships within 4 weeks
AE213 + GM model, 5 to 50 mV/V input range (52C), optional filter (58T), peak and hold alarm output (58C), track/hold display options (58D), 220 vac power supply (60A), custom front panel (51D), rack mount (51A)	AE213 – 52C - 58T - 58C - 58D - 60A - 51D- 51A	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Model	GM		
Input range	0.5 to 5 mv/v	52C: 5 to 50 mv/v	
Analog output	Filter setting (260 Hz)	58T optional filter: 10, 30, 10K, 27K Hz	
Alarm output	58A: high low limits	58C: Peak and hold 58M: Knob pot and span adjustment	
Display options	58C: peak / hold	58D: track/ hold	
Power supply	110 Vac	60A: 220 Vac 60C: Battery power 56A: 4 to 20 Ma output	
Front panel			51D: custom
Mounting option		51A: Rack Mount 51C: NEMA enclosure.	

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.