

Delivery Program

Product Category:	Load Cells
Model:	11 Subminiature
Order Code(s):	BL321

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BL321 +250 g load range (AN), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), and Phoenix connect on end of cable (6v)	BL321 – AN – 1a – 2u – 6v	Fast-track manufacture, ships within 4 weeks
BL321 +500 g (AP), 30 °F to 130 °F (1b), Unamplified, mV/V output (2u), and Teflon integral cable (6e)	BL321 – AP – 1b – 2u – 6e	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load range		250g (AN), 5 lb (AT), 25 lb (BL), 100 lb (BR)	150g (AL), 500g (AP), 1000g (AR), 10 lb (AV), 50 lb (BN), 250 lb (CN), 500 lb (CR), 1000 lb (CV)
Temperature compensation		1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F	
Internal amplifiers		2u. Unamplified, mV/V output *	
Electrical termination		5 ft integral cable with balance board * 6a. Bendix PTIH-10-6P - (or equivalent) 6 pin (max. 120 °C) on end of cable 6v. Phoenix connector on end of cable	6e. Integral cable: Teflon
Electrical termination orientation			15d. Connector on end of cable
Special calibration		30a. Compression testing only, positive in compression 30b. Tension and compression testing only, positive in tension 30c. Compression testing only, negative in compression	
Shock and vibration			44a. Shock and vibration resistance

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.