

Delivery Program

Product Category:	Load Cells
Model:	129
Order Code(s):	BL808

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BL808 + 1000 kg load range (LQ) , -20 °C to 55 °C, Unamplified, mV/V output (2u), and 5 m of flying leads electrical termination	BL808 – LQ – 2u	Quick ship, ships in 1 to 5 days
BL808 + 5000 kg load range (LU) , -20 °C to 55 °C, Unamplified, mV/V output (2u), and 5 m of flying leads electrical termination	BL808 – LU – 2u	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load range	1000kg (LQ), 2000kg (LS), 3000kg (LT)		5000kg (LU)
Temperature compensation	-20 °C to 55 °C, [-4 °F to 131 °F] *		
Internal amplifiers	2u . Unamplified, mV/V output *		
Electrical termination	5 m flying leads *		

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.