

## Delivery Program

<b>Product Category:</b>	Load Cells
<b>Model:</b>	3140
<b>Order Code(s):</b>	3140

### USE THE CHART BELOW TO DETERMINE LEAD TIMES<sup>1</sup>

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
3140 + enhanced accuracy (P), 300 lb load range (300)	3143 – P – 300	Build-to-order, call Honeywell for lead time

Model 3149-FR series are low capacity low accuracy fatigue rated series of load cells

Model 3140-P series are an enhanced accuracy rated load cell

Model 3140-CS series are an enhanced accuracy rated load cell that can be used for calibration standards

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load range			Model 3143-P-300: 300 lbs Model 3143-P-500: 500 lbs Model 3143-P-1K: 1000 lbs Model 3143-P-2K: 2000 lbs Model 3144-P-5K: 5000 lbs Model 3144-P-10K: 10000 lbs Model 3145-P-25K: 25000 lbs Model 3145-P-50K: 50000 lbs Model 3146-P-100K: 100000 lbs Model 3143-CS-300: 300 lbs Model 3143-CS-500: 500 lbs Model 3143-CS-1K: 1000 lbs Model 3143-CS-2K: 2000 lbs Model 3144-CS-5K: 5000 lbs Model 3144-CS-10K: 10000 lbs Model 3145-CS-25K: 25000 lbs Model 3145-CS-25K: 25000 lbs Model 3145-CS-50K: 50000 lbs Model 3146-CS-100K: 100000 lbs Model 3149-FR-50: 50 lbs Model 3149-FR-100: 100 lbs Model 3149-FR-300: 300 lbs

<sup>1</sup> LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

**Options:** for special options or metric versions consult factory.

**Accessories offered:** mating connector/cable assembly, load button, rod end bearing

*Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.*