

Delivery Program

Product Category:	Load Cells
Model:	53 Low Cost
Order Code(s):	AL131

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AL131 + 500 lb load range (CR), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), and Teflon cable (6e)	AL131 – CR – 1a – 2u – 6e	Quick ship, ships in 1 to 5 days
AL131 + 500 lb load range (CR), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), and Phoenix connect on end of cable (6v),	AL131 – CR – 1a – 2u – 6v	Fast-track manufacture, ships within 4 weeks
AL131 + 5 lb load range (AT), 30 °F to 130 °F (1b), Unamplified, mV/V output (2u), and PVC integral cable (6f)	AL131 – AT – 1b – 2u – 6f	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load ranges	500 (CR), 1000 (CV), 2000 (DL), 5000 (DR), 10000 (DV), 20000 (EL), 50000 lb (EP)	7500 lb (DT)	5 (AT), 10 (AV), 25 (BL), 50 (BN), 100 (BR), 250 (CN), 3000 (DN), 4000 (DP), 15000 (EJ), 30000 lb (EN)
Temperature compensation	1a. 60 °F to 160 °F *	1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F	1i. -65 °F to 250 °F 1j. 0 °C to 50 °C 1k. -20 °C to 85 °C 1m. -25 °C to 110 °C
Internal amplifiers	2u. Unamplified, mV/V output *		
Electrical termination	6e. Integral cable Teflon *	6v. Phoenix connector on end of cable	6d. Microtec DR-4S-4H 4-pin 6f. Integral cable: PVC 6g. Integral cable: Neoprene 6h. Integral cable: Silicone 6i. Integral underwater cable
Special calibration		9a. 10 point (5 up/5 down) 20 % increments @68 °F 9b. 20 point (10 up/10 down) 10 % increments @68 °F	
Electrical termination orientation			15d. connector on end of cable
Shock and vibration			44a. Shock and vibration resistance
Interfaces		53e. Signature calibration (inline module only) 53t. TEDS IEEE 1451.4 module (external only)	

(continued)

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* *Default options.*

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.