

Delivery Program

Product Category:	Load Cells
Model:	AL-SC
Order Code(s):	TL131

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
TL131 + 500 lb load range (CR), -12 °C to 49 °C, Unamplified, mV/V output (2u), 1 ft cable with MS3100A-14S-5P, and compression only calibration (30a)	TL131 – CR – 2u – 30a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load ranges			500 lb (CR), 1000 lb (CV), 2000 lb (DL)
Temperature compensation			-12 °C to 49 °C [10 °F to 120 °F]
Internal amplifiers			2u. Unamplified, mV/V output *
Electrical termination			1 ft cable with MS3100A-14S-5P connector attached
Special calibration			30a. Compression only calibration, positive in compression) 30b. Tension and compression calibration, positive in tension 30c. Compression only calibration, negative in compression

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMCatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.