

Delivery Program

Product Category:	Load Cells
Model:	D
Order Code(s):	BL913

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BL913 + 150 g load range (AL), 30 °F to 130 °F (1b), Unamplified, mV/V output (2u), and Teflon integral cable (6e)	BL913 – AL – 1b – 2u – 6e	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Load ranges			150 g (AL), 250 g (AN), 500 g (AP), 1000 g (AR), 5 (AT), 10 (AV), 25 (BL), 50 (BN), 100 (BR), 250 (CN), 500 (CR), 1000 (CV), 2000 (DL), 3000 (DN), 5000 (DR), 7500 (DT), 10000 (DV), 15000 (EJ), 20000 (EL), 30000 lb (EN)
Temperature compensation			1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F 1g. 70 °F to 325 °F 1h. 70 °F to 400 °F 1i. -65 °F to 250 °F
Internal amplifiers			2u. Unamplified, mV/V output *
Electrical termination			6e. Integral cable: Teflon (5 ft) * 6a. Bendix PTIH-10-6P (or equivalent), 6-pin (max. 250 °F) on end of cable 6v. Phoenix connector on end of cable 6i. Integral underwater cable
Electrical termination orientation			15d. Connector on end of cable
Load direction			30a. Positive in compression, compression testing only * 30c. Negative in compression, compression testing only
Shock and vibration			44a. Shock and vibration resistance
Interfaces			53s. Signature calibration (Inline module only) 53t. TEDS IEEE 1451.4 module (external only)

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.