

Delivery Program

Product Category:	Load Cells
Model:	RH
Order Code(s):	AL419

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AL419 + 2K load range (DJ), 30 °F to 130 °F (1b), Unamplified, mV/V output (2u), PVC integral cable (6f), and radially electrical exit (15c)	AL419 – DJ – 1b – 2u – 6f – 15c	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)														
Load ranges			2K (DJ), 3K (DN), 4K (DP), 5K (DR), 7.5K (DT), 10K (DV), 15K (EJ), 20K (EL), 30K (EN), 50K (EP), 75K (ER), 100K (ET), 150K (FJ), 200K (FL)														
Temperature compensation			<table border="0"> <tr> <td>1a. 60 °F to 160 °F *</td> <td>1g. 70 °F to 325 °F</td> </tr> <tr> <td>1b. 30 °F to 130 °F</td> <td>1h. 70 °F to 400 °F</td> </tr> <tr> <td>1c. 0 °F to 185 °F</td> <td>1i. -65 °F to 250 °F</td> </tr> <tr> <td>1d. -20 °F to 130 °F</td> <td>1j. 0 °C to 50 °C</td> </tr> <tr> <td>1e. -20 °F to 200 °F</td> <td>1k. -20 °C to 85 °C</td> </tr> <tr> <td>1f. 70 °F to 250 °F</td> <td>1m. -25 °C to 110 °C</td> </tr> </table>	1a. 60 °F to 160 °F *	1g. 70 °F to 325 °F	1b. 30 °F to 130 °F	1h. 70 °F to 400 °F	1c. 0 °F to 185 °F	1i. -65 °F to 250 °F	1d. -20 °F to 130 °F	1j. 0 °C to 50 °C	1e. -20 °F to 200 °F	1k. -20 °C to 85 °C	1f. 70 °F to 250 °F	1m. -25 °C to 110 °C		
1a. 60 °F to 160 °F *	1g. 70 °F to 325 °F																
1b. 30 °F to 130 °F	1h. 70 °F to 400 °F																
1c. 0 °F to 185 °F	1i. -65 °F to 250 °F																
1d. -20 °F to 130 °F	1j. 0 °C to 50 °C																
1e. -20 °F to 200 °F	1k. -20 °C to 85 °C																
1f. 70 °F to 250 °F	1m. -25 °C to 110 °C																
Internal amplifiers			<table border="0"> <tr> <td>2u. Unamplified, mV/V output*</td> <td>2j. 4 mA to 20 mA (three-wire) output</td> </tr> <tr> <td>2b. 4 wire, ±5 Vdc output</td> <td>2k. 4 mA to 20 mA (two-wire)</td> </tr> <tr> <td>2c. 0 Vdc to 5 Vdc</td> <td>2t. 0 Vdc to 10 Vdc output</td> </tr> <tr> <td></td> <td>2n (2N) 4 mA to 20 mA (two-wire) intrinsically safe</td> </tr> </table>	2u. Unamplified, mV/V output*	2j. 4 mA to 20 mA (three-wire) output	2b. 4 wire, ±5 Vdc output	2k. 4 mA to 20 mA (two-wire)	2c. 0 Vdc to 5 Vdc	2t. 0 Vdc to 10 Vdc output		2n (2N) 4 mA to 20 mA (two-wire) intrinsically safe						
2u. Unamplified, mV/V output*	2j. 4 mA to 20 mA (three-wire) output																
2b. 4 wire, ±5 Vdc output	2k. 4 mA to 20 mA (two-wire)																
2c. 0 Vdc to 5 Vdc	2t. 0 Vdc to 10 Vdc output																
	2n (2N) 4 mA to 20 mA (two-wire) intrinsically safe																
Electrical termination			<table border="0"> <tr> <td>6a. Bendix PTIH-10-6P (or equivalent) 6-pin (ranges < 50000) *</td> <td>6f. Integral cable: PVC</td> </tr> <tr> <td>6b. MS connector MS3102E-14S-6P (mates with MS3106E-14S-6S, max 160 °F) (ranges > 50000 lb)*</td> <td>6g. Integral cable: Neoprene</td> </tr> <tr> <td>6e. Integral cable: Teflon</td> <td>6h. Integral cable: Silicone</td> </tr> <tr> <td></td> <td>6i. Integral underwater cable</td> </tr> <tr> <td></td> <td>6j. 1/2-14 conduit fitting with 5 ft of 4 conductor PVC cable</td> </tr> <tr> <td></td> <td>6q. Molded integral cable: Polyurethane</td> </tr> <tr> <td></td> <td>6v. Phoenix connector on end of cable</td> </tr> </table>	6a. Bendix PTIH-10-6P (or equivalent) 6-pin (ranges < 50000) *	6f. Integral cable: PVC	6b. MS connector MS3102E-14S-6P (mates with MS3106E-14S-6S, max 160 °F) (ranges > 50000 lb)*	6g. Integral cable: Neoprene	6e. Integral cable: Teflon	6h. Integral cable: Silicone		6i. Integral underwater cable		6j. 1/2-14 conduit fitting with 5 ft of 4 conductor PVC cable		6q. Molded integral cable: Polyurethane		6v. Phoenix connector on end of cable
6a. Bendix PTIH-10-6P (or equivalent) 6-pin (ranges < 50000) *	6f. Integral cable: PVC																
6b. MS connector MS3102E-14S-6P (mates with MS3106E-14S-6S, max 160 °F) (ranges > 50000 lb)*	6g. Integral cable: Neoprene																
6e. Integral cable: Teflon	6h. Integral cable: Silicone																
	6i. Integral underwater cable																
	6j. 1/2-14 conduit fitting with 5 ft of 4 conductor PVC cable																
	6q. Molded integral cable: Polyurethane																
	6v. Phoenix connector on end of cable																
Electrical termination orientation			<table border="0"> <tr> <td>15a. Horizontal electrical exit port orientation *</td> </tr> <tr> <td>15b. Vertical electrical exit port orientation</td> </tr> <tr> <td>15c. Radial electrical exit port orientation</td> </tr> <tr> <td>15d. Connector on end of cable</td> </tr> </table>	15a. Horizontal electrical exit port orientation *	15b. Vertical electrical exit port orientation	15c. Radial electrical exit port orientation	15d. Connector on end of cable										
15a. Horizontal electrical exit port orientation *																	
15b. Vertical electrical exit port orientation																	
15c. Radial electrical exit port orientation																	
15d. Connector on end of cable																	
Internal amp enhancements			<table border="0"> <tr> <td>3a. Input/output isolation</td> </tr> <tr> <td>3d. Remote buffered shunt calibration</td> </tr> </table>	3a. Input/output isolation	3d. Remote buffered shunt calibration												
3a. Input/output isolation																	
3d. Remote buffered shunt calibration																	
Shunt calibration			8a. Precision internal resistor														
Bridge type			<table border="0"> <tr> <td>11a. Square bridge</td> <td>11c. Square and symmetrical bridge</td> </tr> <tr> <td>11b. Symmetrical bridge</td> <td>31a. Dual bridge</td> </tr> </table>	11a. Square bridge	11c. Square and symmetrical bridge	11b. Symmetrical bridge	31a. Dual bridge										
11a. Square bridge	11c. Square and symmetrical bridge																
11b. Symmetrical bridge	31a. Dual bridge																
Bridge resistance			12b. 5000 ohm														
Zero & span adj.			14a. No access to zero and span adjustment														
Interfaces			<table border="0"> <tr> <td>53e. Signature calibration (inline module available)</td> </tr> <tr> <td>53t. TEDS IEEE 1451.4 module</td> </tr> </table>	53e. Signature calibration (inline module available)	53t. TEDS IEEE 1451.4 module												
53e. Signature calibration (inline module available)																	
53t. TEDS IEEE 1451.4 module																	

(continued)

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* *Default options.*

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.