

Delivery Program

Product Category:	Pressure Transducers
Model:	355
Order Code(s):	BP313

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BP313 + 500 psi pressure range (CR), 30 °F to 130 °F (1b), 0 Vdc to 5 Vdc internal amplifier (2c), 7/16-20 UNF male pressure port (5d), and Teflon integral cable (6e)	BP313 – CR – 1b – 2c – 5d – 6e	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges			500 (CR), 750 (CT), 1000 (CV), 1500 (DJ), 2000 (DL), 2500 (DM), 3000 (DN), 5000 (DR) psi
Temperature compensation			1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F
Internal amplifiers			2c. 0 Vdc to 5 Vdc 2k. 4 mA to 20 mA, two-wire output 2n. (2N) 4 mA to 20 mA (two-wire output), intrinsically safe
Pressure ports			5d. 7/16 -20 UNF male * 5p. M12 x 15 male
Electrical termination			6a. Bendix PTIH-10-6P (or equivalent) 6 pin (max 250 °F) * 6e. Integral cable: Teflon (-54 °C to 245 °C) 6f. Integral cable: PVC (-30 °C to 70 °C) 6h. Integral cable: Silicone (-54 °C to 150 °C) 6i. Integral underwater cable, 8m (max. 80 °C) 6n. DIN 40050 6q. Molded integral cable: Polyurethane 6v. Phoenix connector on end of cable
Special calibration			9a. 10 point (5 up/5 down) 20 % increments @ 20 °C 9b. 20 point (10 up/10 down) 10 % increments @ 20 °C 9e. CE mark
Interfaces			53t. TEDS IEEE 1451.4 module

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMCatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.