

Delivery Program

Product Category:	Differential Pressure
Model:	420 DP Mid
Order Code(s):	AD412

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AD412 + 50 psid pressure range (BN) , 30 °F to 130 °F (1b), 4 mA to 20 mA internal amp (2k), 1/8-27 NPT female pressure port (5h), PVC integral cable (6f), and 17-4 stainless steel wetted diaphragm	AD412 – BN – 1b – 2k – 5h – 6f	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges (psid)			50 (BN), 75 (BP), 100 (BR), 150 (CJ), 200 (CL), 300 (CP), 500 (CR), 750 (CT)
Temperature compensation			1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F
Internal amplifiers			2k. 4 mA to 20 mA (two wire) *
Pressure ports			5h. 1/8-27 NPT female * 5c. 7/16-20 UNF female
Electrical termination			6a. Bendix PTIH-10-6P (or equiv.) 6 pin (250 °F) * 6e. Integral cable: Teflon (-54 °C to 245 °C) 6f. Integral cable: PVC (-30 °C to 70 °C) 6g. Integral cable: Neoprene (-20 °C to 80 °C) ¹ 6h. Integral cable: Silicone (-54 °C to 150 °C) 6i. Integral underwater cable (8 m [26 ft]) (max. 80 °C) ¹ 6j. 1/2-14 conduit fitting with 1,5 m [5 ft] 4 conductor PVC cable
Wetted diaphragm			17-4 stainless steel *
Special calibration			9a. 10 point (5 up/5 down) 20% increments @ 20 °C [68 °F] 9b. 20 point (10 up/10 down) 20% increments @ 20 °C [68 °F]
Internal amplifier enhancements			3d. Remote buffered shunt calibration
O ring seals			26a. Metal 26c. Teflon

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMCatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.