

Delivery Program

Product Category:	Pressure Transducers
Model:	811FM
Order Code(s):	BP421 (gage), BP422 (absolute)

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BP421 + 10 psi pressure range (AV), 60 °F to 160 °F (1a), 4 mA to 20 mA, two-wire (2k), 1/4-18 NPT female pressure port (5a), and 0,61 m [2 ft] of 20 GA cable termination (6j)	BP421 – AV – 1a – 2k – 5a – 6j	Fast-track manufacture, ships within 4 weeks
BP421 + 2.5 psi pressure range (AS), 60 °F to 160 °F (1a), 4 mA to 20 mA, two-wire (2k), 1/4-18 NPT female pressure port (5a), and 0,61 m [2 ft] of 20 GA cable termination (6j)	BP421 – AS – 1a – 2k – 5a – 6j	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges		10 (AV), 15 (BJ), 25 (BL), 50 (BN), 75 (BP), 100 (BR), 150 (CJ), 200 (CL), 300 (CP), 500 (CR), 750 (CT), 1000 (CV), 1500 (DJ), 2000 (DL), 3000 (DN), 5000(DR), 7500 (DT), 10000 (DV) psig/a	2,5 (AS) psia/g
Temperature compensation		1a. 60 °F to 160 °F *	
Internal amplifiers		2k. 4 mA to 20 mA, two-wire *	
Pressure ports		5a. 1/4-18 NPT female and 1/2-14 NPT male with 25,4 mm [1 in] hex *	
Electrical termination		6j. 0,61 m [2 ft] of 20 GA cable with ½-14 NPT male conduit *	
Wetted diaphragm			10a. 316 stainless steel

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.