

Delivery Program

Product Category:	Differential Pressure
Model:	911FMD High
Order Code(s):	BD423

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BD423 + 1000 psid pressure range (CV), 60 °F to 160 °F (1a), 4 mA to 20 mA internal amp (2k), 1/4-18 NPT female pressure port (5a), and 22 GA cable with case ground (6j)	BD423 – CV – 1a – 2k – 5a – 6j	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges (psid)			1000 (CV), 2000 (DL), 3000 (DN), 5000 (DR), 7500 (DT), 10000 (DV)
Temperature compensation			1a. 60 °F to 160 °F *
Internal amplifiers			2k. 4 mA to 20 mA (two-wire) *
Pressure ports			5a. 1/4-18 NPT female (2) *
Electrical termination			6j. 22 GA cable with case ground 609,6 mm [2 ft], 1/2 NPT to 14 NPT *
Wetted diaphragm			17-4 PH stainless steel *
Special calibration			9a. 10 point (5 up/5 down) 20% increments @ 20 °C [68 °F] 9b. 20 point (10 up/10 down) 10% increments @ 20 °C [68 °F]

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.