

Delivery Program

Product Category:	Pressure Transducers
Model:	A105a
Order Code(s):	AP313 to AP318

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AP313 + 300 psi pressure range (CP), 60 °F to 160 °F (1a), 4 mA to 20 mA, two-wire output (2k), 7/16-20 UNF male (5d), and Bendix PTIH-10-6P (6a)	AP313 – CP – 1a – 2k – 5d – 6a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges			300 (CP), 500(CR), 1000 (CV), 2000 (DL), 3000 (DN), 5000(DR), 10000 (DV) psi
Temperature compensation			1a. 60 °F to 160 °F 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1j. 0 °C to 50 °C 1k. -20 °C to 85 °C
Internal amplifiers			2k. 4 mA to 20 mA, two-wire output 2c. 1 Vdc to 5 Vdc 2t. 1 Vdc to 10 Vdc output
Pressure ports			5d. 7/16-20 UNF male * 5p. M12 x 1.5
Electrical termination			6a. Bendix PTIH-10-6P (or equivalent) 6 pin (max 120 °C) * 6e. Integral cable: Teflon (-54 °C to 245 °C) 6f. Integral cable: PVC (-30 °C to 70 °C) 6h. Integral cable: Silicone (-54 °C to 150 °C) 6i. Integral underwater cable: (max 80 °C) 6v. Phoenix connector on end of cable
Special calibration			9a. 10 point (5 up/5 down) 20 % increments @ 20 °C 9b. 20 point (10 up/10 down) 10 % increments @ 20 °C

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.