

Delivery Program

Product Category:	Pressure Transducers
Model:	A-205
Order Code(s):	AP312

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AP312 + 200 psi pressure range (CL), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), 1/4-18 NPT male (5b), and Bendix PTIH-10-6P (6a)	AP312 – CL – 1a – 2u – 5b – 6a	Fast-track manufacture, ships within 4 weeks
AP312 + 500 psi pressure range (CR), 70 °F to 325 °F (1g), Unamplified, mV/V output (2u), 1/4-18 NPT male (5b), and Bendix PTIH-10-6P (6a)	AP312 – CR – 1g – 2u – 5b – 6a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges		100 (BR), 150 (CJ), 200 (CL), 300 (CP), 500 (CR), 1000 (CV), 2000 (DL), 3000 (DN), 5000 (DR), 10000 (DV) psi	500 (CR), 750 (CV), 1500 (DJ), 7500 (DT) psi
Temperature compensation		1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F 1i. -65 °F to 250 °F	1g. 70 °F to 325 °F 1h. 70 °F to 400 °F
Internal amplifiers		2u. Unamp., mV/V output *	
Pressure ports		5b. 1/4-18 NPT male *	
Electrical termination		6a. Bendix PTIH-10-6P (or equivalent) 6 pin (max 400 °F) * 6e. Integral cable: Teflon (-65 °F to 475 °F) 6h. Integral cable: Silicone (-65 °F to 300 °F) 6i. Integral underwater cable: (max 180 °F) 6v. Phoenix connector on end of cable	
Special calibration		9a. 10 point (5 up/5 down) 20 % increments @ 70 °F 9b. 20 point (10 up/10 down) 10 % increments @ 70 °F	
Wetted diaphragm			10e. Inconel X-750
Shock and vibration			44a. Shock and vibration resistance

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.