

Delivery Program

Product Category:	Pressure Transducers
Model:	Accu-Gage
Order Code(s):	AG401, AG402

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AG401 gage + 25 psi pressure range (BL), 1/4-18 NPT male (5a), 60 °F to 105 °F (1a), and 0.10 % accuracy	AE441– BL – 5a – 1a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Order codes			AG400 gage: AE435 AG400 absolute: AE436 AG400 vacuum: AE437 AG401 gage: AE441 AG401 absolute: AE442 AG401 vacuum: AE443
Pressure ranges for Model AG400			15 (BJ) psig/a/v 25 (BL), 50 (BN), 75 (BP), 100 (BR), 200 (CL), 300 (CP), 500 (CR), 750 (CT), 1000 (CV), 1500 (DJ), 2000 (DL), 3000 (DN) 5000 (DR), 7500 (DT), 10000 (DV), 15000 (EJ) psig/a
Pressure ranges for Model AG401			15 (BJ) psig/a/v 25 (BL), 50 (BN), 75 (BP), 100 (BR), 200 (CL), 300 (CP), 500 (CR), 750 (CT), 1000 (CV), 1500 (DJ), 2000 (DL), 3000 (DN) 5000 (DR), 7500 (DT), 10000 (DV), 15000 (EJ), 60000 (ES) psig/a
Pressure Port			5a. 1/4-18 NPT male (15 to 1000 psi) * 5b. 1/4-18 NPT female (1500 to 10k psi) * 5u. 9/16-18 UNF female (AE f-250-C) (15K to 60K psi) *
Temperature, operating			1a. 60 °F to 105°F *
Accuracy			AG400: 0.05 % * AG401: 0.10 % *
Special features			Field selectable engineering units Auto-zero Tare Hi/lo limits Peak/valley hold on input channels

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

*Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.