

Delivery Program

Product Category:	Pressure Transducers
Model:	BDR
Order Code(s):	BP217

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BP217 + 150 psi pressure range (CJ), 60 °F to 160 °F (1a), ±5 Vdc internal amplifier (2d), 1/4-18 NPT male pressure port (5b), and Bendix PTIH-10-6P termination (6a)	BP217 – CJ – 1a – 2d – 5b – 6a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges			150 (CJ), 200 (CL), 300 (CP), 500 (CR), 750 (CT), 1000 (CV), 1500 (DJ), 2000 (DL), 2500 (DM), 3000 (DN), 5000 (DR), 7500 (DT), 10000 (DV), 15000 (EJ) psig
Temperature compensation			1a. 60 °F to 160 °F * 1j. 0 °C to 50 °C 1k. -20 °C to 85 °C 1m. -25 °C to 100 °C
Internal amplifiers			2d. ±5 Vdc 2p. 4 mA to 20 mA (two wire output)
Pressure ports			5b. 1/4-18 NPT male *
Electrical termination			6a. Bendix PTIH-10-6P (or equivalent), 6 pin (max 250 °F) * 6m. DIN 43650 6n. DIN 40050 6q. Molded integral cable: Polyurethane

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.