

## Delivery Program

<b>Product Category:</b>	Pressure Transducers
<b>Model:</b>	CIP Ultra
<b>Order Code(s):</b>	CP100 (gage), CP101 (absolute) CP200 (gage), CP201 (absolute) CP300 (gage), CP301 (absolute)

### USE THE CHART BELOW TO DETERMINE LEAD TIMES<sup>1</sup>

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
CP100 + 10 psi pressure range ( <b>AV</b> ), -1 °C to 82 °C, Intrinsically safe amp 4 mA to 20 mA, ( <b>2n(2N)</b> ), 1.5 in Triclover ( <b>16b</b> ), and Bendix PTIH-10-6P ( <b>6a</b> )	CP100 – <b>AV</b> – <b>2n(2N)</b> – <b>16b</b> – <b>6a</b>	<b>Build-to-order, call Honeywell for lead time</b>

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
<b>Pressure ranges</b>			10 ( <b>AV</b> ), 15 ( <b>BJ</b> ), 25 ( <b>BL</b> ), 50 ( <b>BN</b> ), 100 ( <b>BR</b> ), 200 ( <b>CL</b> ), 250 ( <b>CN</b> ), 400 ( <b>CQ</b> ), 500 ( <b>CR</b> ), 600 ( <b>BS</b> ) psi
<b>Temperature compensation</b>			-1 °C to 82 °C [30 °F to 180 °F] * 1i. -54 °C to 121 °C [-65 °F to 250 °F]
<b>Internal amplifiers</b>			<b>2n(2N)</b> . Intrinsically safe amp 4 mA to 20 mA, two-wire current *
<b>Pressure ports</b>			<b>16b</b> . 1.5 inch Tri-clover * <b>16c</b> . 2 inch Tri-clover <b>16d</b> . 2.5 inch Tri-clover <b>16e</b> . 3 inch Tri-clover
<b>Electrical termination</b>			<b>6j</b> . 1/2-14 NPT conduit fitting with 1,5 m [5 ft] of four conductor PVC cable * <b>6a</b> . Bendix PTIH-10-6P or equivalent 6 pin <b>6m</b> . DIN 43650 <sup>8</sup> <b>6n</b> . DIN 40050
<b>Internal amplifier enhancements</b>			Special filtering
<b>Shunt calibration</b>			<b>3d</b> . Remote buffered shunt calibration
<b>Special calibration</b>			Compound, vacuum, barometric Bar
<b>Wetted diaphragm</b>			<b>10c</b> . Hastelloy C-276
<b>Bridge resistance</b>			<b>12b</b> . 5000 ohm (foil) (max. 121 °C [250 °F])
<b>Zero and span adjustments</b>			<b>14b</b> . Top access to pots

<sup>1</sup> LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

\* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catalogpages.asp>.