

Delivery Program

Product Category:	Pressure Transducers
Model:	DS
Order Code(s):	AP611 (gage); AP612 (absolute) AP613 (gage); AP614 (absolute)

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
AP611 + 5 psi pressure range (AT), 0 °F to 185 °F (1c), RS-232 internal amplifier, 1/4-18 NPT female (5a), and Bendix PT02-12-8P	AP611 – AT – 1c – 5a	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges			5 (AT), 15 (BJ), 30 (BM), 50 (BN), 100 (BR), 150 (CJ), 250 (CN), 500 (CR), 750 (CT), 1000 (CV), 2500 (DM) psig/a
Temperature compensation			4 °C to 60 °C [40 °F to 140 °F] 1c. 0 °F to 185 °F 1k. -20 °C to 85 °C [-4 °F to 185 °F]
Internal amplifiers			RS-485 or RS-232, 0 Vdc to 5 Vdc (non-isolated)
Pressure ports			5a. 1/4-18 NPT female 5b. 1/4-18 NPT male 5c. 7/16-20 UNF female (per MS33649-4) 5d. 7/16-20 UNF male (per MS33656E4)
Electrical termination			Bendix PT02-12-8P (or equiv), 8 pin (max. 121 °C [250 °F])

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.