

Delivery Program

Product Category:	Pressure Transducers
Model:	G
Order Code(s):	BP386, BP387

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BP386 + 150 psi pressure range (CJ), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), and four twisted leads 1,83 m	BP386 – CJ – 1a – 2u	Build-to-order, call Honeywell for lead time
BP386 + 250 psi pressure range (CN), 60 °F to 160 °F (1a), Unamplified, mV/V output (2u), and four twisted leads 1,83 m	BP386 – CN – 1a – 2u	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks) (.310 size only)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges		150 (CJ), 200 (CL), 300 (CP), 500 (CR), 1000 (CV), 2000 (DL), 3000 (DN), 5000 (DR), 7500 (DT), 10000 (DV) psig	250 (CN), 400 (CQ), 600 (CS), 750 (CT), 1500 (DJ), 2500 (DM), 4000 (DP), 6000 (DS), 15000 (EJ), 20000 (EL) psig
Temperature compensation		1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F	1g. 70 °F to 325 °F 1h. 70 °F to 400 °F 1i. -65 °F to 250 °F
Internal amplifiers		2u. Unamp., mV/V output *	
Electrical termination		Four twisted leads 1,83 m [5 ft] *	6d. Microtec DR-4S-4H 4-pin (max 250 °F) ²

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

*Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.