

## Delivery Program

<b>Product Category:</b>	Pressure Transducers
<b>Model:</b>	IP
<b>Order Code(s):</b>	IPG

### USE THE CHART BELOW TO DETERMINE LEAD TIMES<sup>1</sup>

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
Model IP ( <b>IPG1</b> ), 0.15% accuracy ( <b>1</b> ), 100 psi ( <b>BR</b> ), -10 °C to 80 °C [14 °F to 180 °F] temperature compensation ( <b>1BA</b> ), 4 mA to 20 mA, two wire, CE approval output ( <b>2Y</b> ), 1/4 B female pressure port ( <b>5F</b> ), DIN 43650 standard electrical termination ( <b>6M</b> )	<b>IPG1BR,1BA,2Y,5F,6M</b>	<b>Quick ship, ships in 1 to 5 days</b>
Model IP ( <b>IPG1</b> ), 0.15% accuracy ( <b>1</b> ), 5 psi ( <b>AT</b> ), 4 °C to 60 °C [40 °F to 140 °F] temperature compensation ( <b>1AK</b> ), 4 mA to 20 mA, two wire, CE approval output ( <b>2Y</b> ), 1/4 B female pressure port ( <b>5F</b> ), DIN 43650 standard electrical termination ( <b>6M</b> )	<b>IPG1AT,1AK,2Y,5F,6M</b>	<b>Fast-track manufacture, ships within ten days</b>

	<b>Quick-ship</b> (Ships in 1-5 days)	<b>Fast track manufacture</b> (Ships within ten days)
<b>Accuracy</b>	<b>1.</b> 0.15 % <b>2.</b> 0.25 %	
<b>Pressure ranges</b>	100 psi ( <b>BR</b> ); 150 psi ( <b>CJ</b> ); 200 psi ( <b>CN</b> ); 250 psi ( <b>CN</b> ); 500 psi ( <b>CR</b> ); 750 psi ( <b>CT</b> ); 1000 psi ( <b>CV</b> ); 1500 psi ( <b>DJ</b> ); 2000 psi ( <b>DL</b> ); 3000 psi ( <b>DN</b> ); 5000 psi ( <b>DR</b> ); 7 bar ( <b>NB</b> ); 10 bar ( <b>MH</b> ); 16 bar ( <b>NY</b> ); 25 bar ( <b>NZ</b> ); 40 bar ( <b>PB</b> ); 60 bar ( <b>PC</b> ); 100 bar ( <b>ML</b> ); 160 bar ( <b>PD</b> ); 250 bar ( <b>NG</b> ); 350 bar ( <b>NH</b> )	5 psi ( <b>AT</b> ); 10 psi ( <b>AV</b> ); 15 psi ( <b>BJ</b> ); 25 psi ( <b>BL</b> ); 30 psi ( <b>BM</b> ); 50 psi ( <b>BN</b> ); 75 psi ( <b>BL</b> ); 7500 psi ( <b>DT</b> ); 10000 psi ( <b>DV</b> ); 0.5 bar ( <b>MD</b> ); 1 bar ( <b>ME</b> ); 2 bar ( <b>MF</b> ); 3.5 bar ( <b>NA</b> ); 700 bar ( <b>NH</b> )
<b>Temperature compensation</b>	<b>1BA.</b> -10 °C to 85 °C [14 °F to 185 °F] * <b>1AK.</b> 4 °C to 60 °C [40 °F to 140 °F] **	
<b>Electrical output</b>	<b>2AC.</b> 0.5 Vdc to 4.5 Vdc, CE approval <b>2AD.</b> 0.25 Vdc to 10.25 Vdc, CE approval <b>2Y.</b> 4 mA to 20 mA, two wire, CE approval	
<b>Pressure ports</b>	<b>5B.</b> 1/4 in – 18 NPT male <b>5D.</b> 7/16 in – 20 UNF male <b>5F.</b> 1/4 B female <b>5G.</b> 1/4 B male	
<b>Electrical termination</b>	<b>6M.</b> DIN 43650 standard <b>6N.</b> DIN 40050 (mini)	

\* 100 psi to 5000 psi available in -10 °C to 85 °C [14 °F to 185 °F]

\*\* 5 psi to 75 psi and 7500 psi to 10000 psi (0.5 bar to 3.5 bar, 700 bar) available in 4 °C to 60 °C [40 °F to 140 °F]

<sup>1</sup> LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

*Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.*