

Delivery Program

Product Category:	Pressure Transducers
Model:	LL-V
Order Code(s):	BP712

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BP712 + 1 psi pressure range (AP), 60 °F to 160 °F (1a), 0 Vdc to 5 Vdc output (2c), and flush pressure port	BP712 – AP – 1a – 2c	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Pressure ranges			0 mm to 508 mm [0 in to 20 in] (WC), 0 mm to 762 mm [0 in to 30 in] (WE), 0 mm to 1270 mm [0 in to 50 in] (WG), 0 mm to 2540 mm [0 in to 100 in] (WI), 0 mm to 3048 mm [0 in to 120 in] (WK), 0 mm to 3810 mm [0 in to 150 in] (WM), 0 mm to 5080 mm [0 in to 200 in] (WP), 0 mm to 7620 mm [0 in to 300 in] (WR), 0 mm to 12700 mm [0 in to 500 in] of water column (WS) 1 (AP), 2 (AR), 5 (AT), 10 (AV), 15 (BJ), 25 (BL), 50 (BN) psig
Temperature compensation			1a. 60 °F to 160 °F *
Internal amplifiers			2c. 0 Vdc to 5 Vdc output 2j. 4 mA to 20 mA, three-wire output 2k. 4 mA to 20 mA, two-wire output ⁷
Pressure ports			Flush
Internal amplifier enhancements			3d. Remote buffered shunt calibration

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.