

Delivery Program

Product Category:	Torque
Model:	1804 -1807
Order Code(s):	1804, 1805, 1806, 1807

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
1804 + 100 in-lbs torque range (100)	1804 – 100	Quick ship, ships in 1 to 5 days
1806 + 20,000 in-lbs torque range (20K)	1806 – 20K	Build-to-order, call Honeywell for lead time

1800 Series enhanced accuracy rotary torque transducer

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Torque ranges	Model 1804-100: 100 in-lbs Model 1804-200: 200 in-lbs Model 1804-500: 500 in-lbs Model 1804-1K: 1,000 in-lbs Model 1804-2K: 2,000 in-lbs Model 1805-2K: 2,000 in-lbs Model 1805-5K: 5,000 in-lbs Model 1805-10K: 10,000 in-lbs		Model 1806-20K: 20,000 in-lbs Model 1807-50K: 50,000 in-lbs Model 1807-100K: 100,000 in-lbs

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

Options: for special options or metric versions, consult factory.

Accessories offered: mating connectors/cable assembly, foot mount kits, speed sensor

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.