

Delivery Program

Product Category:	Torque
Model:	366
Order Code(s):	TQ366

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
TQ366 + 0.06 oz-into 0.6 oz-in capacity and $\pm 5\%$ accuracy (0)	366 – 0	Fast-track manufacture, ships within 4 weeks

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Capacity		366-0. 0.06 oz-in to 0.6 oz-in 366-2. 0.01 oz-in to 0.1 oz-in 366-3. 0.003 oz-in to 0.03 oz-in 366-0M. 6 gm-cm to 42 gm-cm 366-2M. 1 gm-cm to 7.5 gm-cm 366-3M. 0.2 gm-cm to 2 gm-cm	
Accuracy		366-0 $\pm 5\%$ 366-2. $\pm 10\%$ 366-3. $\pm 10\%$ 366-0M. $\pm 5\%$ 366-2M. $\pm 10\%$ 366-3M. $\pm 10\%$	

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.