

Delivery Program

Product Category:	Torque
Model:	QFFH-9
Order Code(s):	BT121

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
BT121 + 3000 torque range (TR), 30 °F to 130 °F (1b), Unamplified, mV/V output (2u), and PVC integral cable (6f)	BT121 – TR – 1b – 2u – 6f	Build-to-order, call Honeywell for lead time

	Quick-ship (Ships in 1-5 days)	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Torque range			3000 (TR), 6000 (TT), 12000 (TV), 24000 (TW) in-lb
Temperature compensation			1a. 60 °F to 160 °F * 1b. 30 °F to 130 °F 1c. 0 °F to 185 °F 1d. -20 °F to 130 °F 1e. -20 °F to 200 °F 1f. 70 °F to 250 °F
Internal amplifiers			2u. Unamplified, mV/V output *
Electrical termination			6a. Bendix PTIH-10-6P, 6-pin (max. 121 °C [250 °F]) * 6b. MS connector MS3102E-14S-6P (mates with MS3106E-14S-6S, max 160 °F) 6e. Integral cable: Teflon 6f. Integral cable: PVC 6g. Integral cable: Neoprene 6h. Integral cable: Silicone
Interfaces			53e. Signature calibration 53t. T.E.D.S. IEEE 1451.4 module

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

* Default options.

Note: Before selecting option/s, please refer to the Test and Measurement catalog or product data sheet for special application notes and compatibility. A catalog can be ordered on-line at <https://home.honeywell-online.com/newTMcatalog>. Product data sheets are available on Honeywell's web site at <http://content.honeywell.com/sensing/sensotec/catpages.asp>.