

Delivery Program

Product Category:	Torque
Model:	TMS 9250 Custom Flange
Order Code(s):	92502

USE THE CHART BELOW TO DETERMINE LEAD TIMES¹

The range or option code with the longest lead time dictates the shipping time. Categories shaded in grey are required selections. For example (reference only):

If you build this:	The order configuration is this:	The delivery class is:
Model 92502 Custom Flange Digital Telemetry Torque (92502), .05% Accuracy, 5 °C to 75 °C [40 °F to 170 °F] temperature compensation (1AE), Voltage ±10 V Output (56J) with Sinusoidal Frequency(61A)	92502-XXXFT-LBS,1AE,56J,61A	Build-to-order, call Honeywell for leadtime
Model 92502 Custom Flange Digital Telemetry Torque (92502), .05% Accuracy, 5 °C to 75 °C [40 °F to 170 °F] temperature compensation (1AE), Voltage ±10 V Output (56J) with Sinusoidal Frequency(61A), with dynamic balance to ISO 1940 G2.5 (63A)	92502-XXNm,1AE,56J,61A, 63A	Build-to-order, call Honeywell for leadtime

TMS 9250 Custom Flange Series Digital Telemetry Torque Measurement System

	Fast track manufacture (Ships within 4 weeks)	Build-to-order (Call Honeywell 1-800-848-6564 or +1 614-850-5000)
Order code		Model 92502 Custom Flange Digital Telemetry Torque (92502)
Range		
Temperature Comp.	5 °C to 75 °C [40 °F to 170 °F] (1AE)	
Shunt Cal.Option	Remote buffered shunt calibration (3D)	
Output Signal Settings	Voltage ±10 V (56J); Voltage ±10 V Freq. 10 KHz ±5 KHz (56K); Voltage ±10 V Freq. 60 KHz ±20 KHz (56L); Freq. 10 KHz ±5 KHz (56M); Freq. 60 KHz ±20 KHz (56N); Current loop 4 mA to 20 mA (56P); Current loop 4 mA to 20 mA Freq. 10 KHz ±5 KHz (56R); Current loop 4 mA to 20 mA Freq. 60 KHz ±20 KHz (56S)	
Frequency Output	Sinusoidal wave (61A) Square wave (61B)	
Speed Measure.	Zero velocity speed sensing (62A)	
Mechanical Balance for Rated Speed		Dynamic balance to ISO 1940 G2.5 (63A)

¹ LEAD/SHIPPING TIMES ARE APPROXIMATIONS AND MAY VARY DEPENDING ON PRODUCT AVAILABILITY AND OTHER FACTORS. IN NO EVENT SHALL HONEYWELL BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, EXEMPLARY, OR PUNITIVE DAMAGES, EVEN WHERE HONEYWELL HAS BEEN ADVISED OF, OR IS OTHERWISE AWARE OF, THE POSSIBILITY OF SUCH DAMAGES, FOR FAILURE TO MEET SUCH LEAD / SHIPPING TIMES.

Options: for special options, consult factory.